Solution Dyed Nylon Carpet

Building Product Information Sheet | Class 1 | Version 1.0 | 18 September 2026

Combined information for the Urban Collection solution dyed nylon carpet ranges listed below. Read this sheet with the technical specification and warranty, care and maintenance guide for the exact range supplied.

Product description and identifiers

Urban Collection solution dyed nylon (SDN) broadloom carpets are textile floorcoverings supplied in rolls for interior use. The collection includes cut-pile and loop-pile constructions. Fibre, backing, width, pile weight, use classification and other performance details are defined in the range-specific technical specifications.

Range	Technical specification	Warranty and care
Coastal	Technical specification	Warranty and care
Inner Urban	Technical specification	Warranty and care
Elevate	Technical specification	Warranty and care
Opulent	Technical specification	Warranty and care
Lucia	Technical specification	Warranty and care
Metro	Technical specification	Warranty and care
Provincial	Technical specification	Warranty and care
Cosmo	Technical specification	Warranty and care
Loft	Technical specification	Warranty and care
Adorn	Technical specification	Warranty and care
Earthen	Technical specification	Warranty and care
Essence	Technical specification	Warranty and care
Lush	Technical specification	Warranty and care
Traffic 4m	Technical specification	Warranty and care

Manufacture Location

United Arab Emirates, Urban Flooring, www.urbancollection.co.nz

Importer Details

Urban Flooring / Urban Collection
16 Moncur Place, Middleton, Christchurch 8024, New Zealand
www.urbancollection.co.nz | info@urbancollection.co.nz | 03 930 1206
NZBN: 9429030197374

Relevant Building Code clauses and expected contribution

B2 Durability — B2.3.1(c)

When selected for the intended traffic and installed and maintained as specified, the carpet provides a durable, replaceable floor surface. The five-year durability category applies where the floorcovering is easy to access and replace and loss of required performance is readily detectable in normal use. Product selection, underlay, fixing and maintenance must support that period.

The applicable warranty is stated in each range's technical specification and warranty guide. Warranty coverage, exclusions and residential or commercial use conditions vary by range; a warranty term is separate from the Building Code durability requirement.

C3 Fire affecting areas beyond the fire source — C3.4(b)

Where C3.4(b) applies, select the carpet to meet the critical radiant flux requirement for the building use, location and sprinkler provision. Obtain the relevant fire test report and confirm that it covers the selected carpet, backing, substrate, underlay and installation method. ISO 9239-1 testing is referenced by the Building Code.

Fire performance is range- and assembly-specific. A test standard or an ASTM classification in a technical specification must not be treated as a universal New Zealand fire approval. Confirm the supporting evidence and the proposed compliance pathway before specifying the carpet in a fire-regulated location.

D1 Access routes — D1.3.3(d)

Tufted or loop-pile carpet is listed in D1/AS1 Table 2 as an acceptable slip-resistant walking surface, subject to the table's conditions and slope limits. The carpet must be securely installed, with firm joins and finished edges that do not create trip hazards. Select a range rated for stairs where required. This slip-resistance provision does not extend the product's scope to wet-area installations.

F2 Hazardous building materials — F2.3.1

The carpets contribute to control of indoor emissions through the use of low-emission materials. Urban Collection publishes Green Label Plus certification with its carpet product information. Confirm that the current certificate covers the selected product and backing. Select compatible underlay and adhesives, follow their safety instructions and ventilate during and after installation.

Scope and limitations

Use in interior areas that remain dry in normal service. Select the range according to its published residential or commercial classification, expected traffic and stair suitability. A residential rating does not establish suitability for commercial use.

Do not use as a waterproof surface or in areas subject to persistent moisture. Control moisture in the substrate and building before installation. Protect carpet from prolonged excessive direct sunlight; fade resistance does not mean immunity to colour change.

For heated floors, confirm suitability of the chosen carpet, underlay and fixing system with Urban Flooring and the heating supplier. The combined thermal resistance and operating temperatures must suit the heating design. Follow the applicable commissioning and installation instructions.

Installation requirements

Use a competent carpet installer and follow AS/NZS 2455.1:2007, the applicable range-specific instructions and the project specification. Resolve any conflicting requirements with Urban Flooring before work starts.

Inspect the carpet before cutting or laying. Check the range, colour, batch, quantity and condition against the order. Plan pile direction, seam positions and pattern matching. Allow for the pattern repeat where applicable and confirm appearance across adjoining pieces.

Prepare a clean, dry, sound and suitably even substrate. Verify moisture conditions using the method required for the substrate and installation system. Select an appropriate underlay and fixing method for the carpet, traffic and project requirements.

Use seam sealer on all joins as required by the technical specifications. Secure edges, thresholds and stair details, and avoid loose areas or raised seams. Where adhesive is used, follow the adhesive supplier's requirements for preparation, application, ventilation, curing and return to service.

Maintenance and care

Vacuum regularly, at least twice weekly and more often in heavily trafficked areas. Follow the range's care guide when selecting equipment; Urban Collection recommends avoiding rotating brush bars and beater brushes. Use entrance mats and keep them clean.

Attend to spills promptly. Remove solids and blot liquids with a clean white absorbent cloth; avoid scrubbing. Follow the stain-specific instructions in the linked care guide and obtain professional advice where required.

Arrange professional hot-water extraction cleaning at the intervals in the applicable guide, generally every 12–18 months, and retain cleaning records. Avoid excessive wetting and allow carpet to dry fully. Follow any more demanding commercial maintenance requirements.

Use chair mats beneath chairs with castors. Protect carpet when moving furniture and repair damaged tufts, loose edges or seams promptly. Colour variation, tracking and permanent pile reversal are addressed in the warranty and care guide; check the applicable terms before assessing a claim.

Warnings and bans

None of the listed products are identified in MBIE's published section 26 warnings and bans list checked on 18 September 2026.

Supporting documents

The range table links directly to Urban Collection's technical specifications and combined warranty, care and maintenance downloads. Range names link to their product pages, where Green Label Plus certificates and other supporting documents are available. Read the full warranty terms, conditions and exclusions for the selected range.

MBIE D1/AS1 — access routes and slip resistance

New Zealand Building Code — protection from fire

MBIE warnings and bans

This sheet describes product use and expected contributions to Building Code compliance within the stated scope. Compliance of the completed installation depends on the selected product, supporting evidence, design, installation and maintenance.